

SINGULAR VALUE DECOMPOSITION AND STRUCTURED TOTAL LEAST
NORM FOR APPROXIMATE GREATEST COMMON DIVISOR OF
UNIVARIATE POLYNOMIALS

NURUL AIDA NORDIN

UNIVERSITI TEKNOLOGI MALAYSIA

SINGULAR VALUE DECOMPOSITION AND STRUCTURED TOTAL LEAST
NORM FOR APPROXIMATE GREATEST COMMON DIVISOR OF
UNIVARIATE POLYNOMIALS

NURUL AIDA BINTI NORDIN

A dissertation submitted in fulfillment of the
requirements for the award of the degree of
Master of Science (Mathematics)

Faculty of Science
Universiti Teknologi Malaysia

JUNE 2012

To mak, ayah
abang, akak, adik, kak t
hamzah, irfan

ACKNOWLEDGEMENT

In the name of Allah, The Most Gracious and The Most Merciful. First of all, thanks to Almighty Allah for graciously bestowing me the perseverance to undertake this study.

I would like to express my deepest gratitude to both my supervisor, Associate Professor Dr. Ali Abd. Rahman and Associate Professor Dr. Nor'aini Aris for their continuous support, opinion, guidance, patience and tolerance in completing this dissertation.

A warmest gratitude dedicates to my parents and not to forget to my brothers and sisters for their continuous encouragement, patience and prayers throughout the journey of my study.

Lastly, special thanks are extended to my friends for their cooperation, kindness and assistance.

ABSTRACT

This study presents experimental works on approximate GCD of univariate polynomials. The computation of approximate GCD is required in the case of imperfectly known or inexact data which emerges from physical measurements or previous computation error. SVD of Sylvester matrix is used to determine the degree of the approximate GCD. Then, STLN method is employed to generate an algorithm for solving the minimization problem that is to find the minimum perturbation such that the perturbed polynomials have a nonconstant GCD. The formulation of the STLN algorithm lead to the formation of LSE problem and this is solved using QR factorization. Every computation is done using MATLAB. Once the minimum perturbation is found, a MATLAB toolbox called Apalab is used to determine the coefficients of the approximate GCD. Results from experimental work performed reveal that the STLN algorithm presented is as efficient as the existing minimization algorithms.

ABSTRAK

Kajian ini membentangkan kerja – kerja analisa bagi pembahagi sepunya terbesar anggaran melibatkan polinomial pemboleh ubah tunggal. Pengiraan pembahagi sepunya terbesar adalah diperlukan dalam situasi melibatkan data yang tidak diketahui secara sempurna hasil dari sukatan fizikal atau berlakunya ralat dalam pembundaran data. Penguraian nilai tunggal bagi matriks Sylvester digunakan untuk menentukan darjah pembahagi sepunya terbesar anggaran. Seterusnya, kaedah jumlah norma terkecil berstruktur digunakan untuk menjana algoritma bagi menyelesaikan masalah peminimuman iaitu untuk mencari pengusikan minimum supaya polinomial terusik yang dihasilkan mempunyai pembahagi sepunya terbesar bukan malar. Formulasi algoritma jumlah norma terkecil berstruktur menghasilkan pembentukan masalah kuasa dua terkecil dengan pembatas kesamaan dan ini diselesaikan dengan menggunakan kaedah pemfaktoran QR. Setiap pengiraan dilakukan dengan menggunakan perisian MATLAB. Apabila pengusikan minimum telah didapati, sebuah modul perisian MATLAB yang digelar Apalab digunakan untuk menentukan pekali bagi pembahagi sepunya terbesar anggaran tersebut. Hasil dari kerja – kerja pengiraan yang dilakukan menunjukkan algoritma jumlah norma terkecil berstruktur yang dibentangkan adalah secepat dengan algoritma yang sedia ada.